

Tenda AC8 AC1200 wireless dual band ruter  
2.4+5GHz, 1W/3L, Gbit, 1Ghz cpu 128mb, 4x6dBi  
9V/1A

---

Šifra:

Kategorija proizvoda: Bežično povezivanje

Proizvođač: Tenda

Cena: **3.706,00** rsd.



AC8 is a dual band gigabit wireless router specially designed for family with fibre access. Equipped with gigabit ports to support up to 1000 Mbps bandwidth access. The dual band provide 1167Mbps frequency, fully utilise the gigabit fibre. This router is equipped with 28nm 1 GHz CPU to provide better performance. The integrated dual-band technology combines both 2.4GHz and 5GHz under one Wi-Fi name; The 5GHz frequency band is set as priority and faster signal frequency would be allocated to you automatically by our dynamic optimization system. New designed 6 dBi antennas, meet the coverage requirement for small and medium household. AC8 also support broadband account automatic transfer and other features

Standard&Protocol IEEE802.3, IEEE802.3u, IEEE802.3ab

Interface 1\*10/100/1000Mbps WAN port

3\*10/100/1000Mbps LAN ports

Antenna 4\*6dBi external dual band antennas

Button 1\*WPS/Reset button

Power Input: AC 200-240V—50/60Hz

Output: DC 9V 1A

LED indicator 1\*LED

Dimension 200x127x33.6mm(L\*W\*H)

Wireless Standards IEEE 802.11ac/a/n @5GHz  
IEEE 802.11b/g/n @2.4GHz  
Data Rate 2.4GHz: 300Mbps  
5GHz: 867Mbps  
Frequency 2.4GHz & 5GHz  
Wireless Security WPA-PSK/WPA2-PSK, WPA/WPA2  
Wireless Security : Enable /Disable  
Internet Connection Type PPPoE, Dynamic IP, Static IP  
Support automatic access detection  
Supports broadband account automatic transfer  
Operating Mode Wireless Router Mode  
AP Mode  
Universal Repeater mode  
WISP Mode  
DHCP DHCP Server  
DHCP Client List  
DHCP Reservation  
Virtual Server Port Forwarding  
DMZ Host  
UPnP  
Security Client Filter(supports black list and white list)  
Parental Control(supports black list and white list)  
Remote Web Management  
Firewall Forbid WAN PING from internet  
DDNS Support DynDNS, 88ip  
Other Function Broadband management  
MAC address clone  
Static Routing  
System Log  
Backup & Restore configurations  
Firmware upgrade from local  
Temperature Operating Temperature: 0? ~ 40?  
Storage Temperature: -40? ~ 70?  
Humidity Operating Humidity: 10% ~ 90% RH non-condensing  
Storage Humidity: 5% ~ 90% RH non-condensing.  
Default Settings Default Access: tendawifi.com or http://192.168.0.1  
Certification CE, FCC, CCC, SRRC  
Package Content Wireless Router\*1  
Gigabit Ethernet Cable\*1  
Power Adapter\*1  
Installation Guide\*1